



[DOWNLOAD SPECS](#)

## imagePROGRAF PRO-2600

### Specifications

<b>Print Head</b>	PF-10
<b>Number of Nozzles</b>	18,432 nozzles
<b>Droplet Size</b>	4 pl per Colour
<b>Ink Type</b>	Pigment: BK, MBK, C, M, Y, PC, PM, GY, PGY, R, B, +CO
<b>Ink Tank</b>	Shipped with: 160 ml of each colour MBK, BK, C, M, Y, GY, PGY, PC, PM, R, B, CO Replacement: <ul style="list-style-type: none"> <li>• 160 ml PFI-3100 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 160 ml PFI-2100 (MBK)</li> <li>• 330 ml PFI-3300 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 330 ml PFI-2300 (MBK)</li> <li>• 700 ml PFI-3700 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 700 ml PFI-2700 (MBK)</li> </ul>
<b>Printer RAM</b>	Standard Memory: 3 GB Hard Disk: 500 GB
<b>Media Feed</b>	Front-Loading Roll Feed: One Roll, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)
<b>Media Width</b>	Roll Feed: 6" - 24" (152.4 mm - 610 mm) Cut Sheet: 6" - 24" (152.4 mm - 610 mm)
<b>Media Cutter</b>	Automatic horizontal cutting (Rotary cutter): standard
<b>Media Thickness</b>	0.002" - 0.03" (0.07 mm - 0.8 mm)
<b>Media Core Sizes</b>	2" Core Standard. 2"/3" Core Roll Holder Set PRO-2600 (RH2-29), PRO-4600 (RH2-46), PRO-6600 (RH2-66)
<b>Maximum Roll Outer</b>	6.7" or less (170 mm or less)

## Diameter

---

**Media Output** Catch Basket

---

**Printing Software Utilities** Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout

---

**Operating System** Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit)

Macintosh OS v10.12.6 - v13x

---

**Print Language** SGRaster (Swift Graphic Raster), PDF, JPEG

---

**Interface** Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX,  
Wireless LAN (IEEE 802.11 b/g/n)\*  
\*Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

---

**Power Supply** AC 100 - 240V (50 - 60 Hz)

---

**Power Consumption** Max: Approx 85W  
Standby: Approx. 1.7W  
Power Off: Approx 0.1W

---

**Certifications** ENERGY STAR® (Worldwide), EPEAT Gold

---

**Operational Environment** Temperature: 59 - 86 °F (15 - 30 °C)  
Relative Humidity: 10 - 80% (Non Condensation)

---

**Printer Dimensions (W x D x H) and Weight** With stand and basket open: 43.7" x 38.7" x 46", 225 lbs  
Main unit with pallet: 52.1" x 35.9" x 44.8", 346.1 lbs

---

**Options**

- Multifunction Roll Unit - PRO-2600 (RU-23) & PRO-4600 (RU-43)
- 2/3" Roll Holder Set PRO-2600

---

**User-replaceable items**

- Ink Tank: PFI-3100 (160 ml)/PFI-2100 MBK (160 ml), PFI-3300 (330 ml)/ PFI-2300 MBK (330 ml), PFI-3700 (700 ml)/PFI-2700 MBK (700 ml)
- Print Head (PF-10)
- Maintenance Cartridge (MC-30)
- Cutter Blade (CT-07)

---